

Technical information

Diptank 200A

Diptank 200A+



Characteristics

- Automatic platform with conveyor belt
- Digital temperature control
- Pneumatic operation
- Stainless steel casing
- Optimal hygiene
- Maximum loading capacity: 50 kg
- Immersion depth: 200 mm
- Immersion time: 2-5 seconds (adjustable)
- Cycle time: 200A: 22 sec. / 200A+: 15 sec.
- Compressed air consumption 50 l/min 6 bar
- Fully insulated
- Vapour exhaust ø125 mm, excl. fan
- Automatically controlled water supply
- Water drain
- Automatic water level control
- Built-in scale protection
- Transfer function (passthrough without dipping)
- Time switch to preheat water
- Potential-free contact



Specs	Diptank 200A	Diptank 200A+
Sound emission (dB(A))	<70	
Dip cycle time (sec.)	2-5	
Machine cycle 50 / 60Hz (sec.)	22	15
Machine dimensions LxWxH (mm)	1170x1700x1350	
Maximum packaged food product dimensions LxWxH (mm)	1098x575x200	
Weight machine (kg.)	310	
Weight conveyor (kg.)	15	
Water capacity (L)	300	
Maximum loading capacity (kg.)	50	
Supply voltage, frequency	3 x 380 V, 60 Hz 3 x 400 V, 50 Hz	3 x 400 V, 50 Hz 3 x 440 V, 60 Hz
Power (kW)	20,0	36,5

Dimensions mm

